



BLAST SPRAYABLE®

17-0-0

Guaranteed Analysis:
Total Nitrogen (N) 17%
17% Urea Nitrogen

Derived from Urea Hydrochloride
F002833

For chemical emergency spill, leak, fire, exposure or accident, call CHEMTEL day or night.
Domestic North America 800-255-3924. International call 813-248-0585 (collect calls accepted).

KEEP OUT OF REACH OF CHILDREN DANGER

Read entire label for additional precautionary statements.
FOR PROFESSIONAL OR INDUSTRIAL USE ONLY.



DANGER
Toxic if swallowed.
Causes severe skin and eye damage.

NET CONTENTS: 30 GALLONS (113.5 L)

Net Weight: 300 lbs (136.3 kgs)

Density: 10 lbs/gal (1.2 kg/ltr)



8 10950 02037 5

LOT NO:



1273 Imperial Way Paulsboro, NJ 08066 USA
1-800-257-7797 | aquatrols.com

04/27/2020

Blast® Sprayable is an advanced sprayable acid, combining the performance of a strong mineral acid with ease of handling and greater safety. Blast Sprayable will dissolve carbonates in the soil, opening up soil pores.

Directions for Use

WHAT IT DOES:	Blast Sprayable is designed to dissolve carbonate build up in the soil.
WHERE AND WHEN TO USE	Blast Sprayable is recommended for use on fine turfgrasses such as those found on golf courses, athletic fields, residential and commercial and other highly maintained turf areas.
APPLICATION RATES AND FREQUENCY	Apply Blast Sprayable at 32 to 64 fl oz/acre. Product should be applied with a spray volume of 50 gallons of water per acre for fairways and 88 gallons of water per acre for greens. Apply once a week for three weeks to get initial effect and then apply every two weeks as needed through the growing season. After spray application, immediately irrigate the area lightly to wash Blast Sprayable off the canopy and into the soil profile.
GOLF BUNKERS:	For use in sand bunkers that have become crusted and hardened. Blast Sprayable is a calcium carbonate-dissolving product that reduces the impact of high bicarbonate, high hardness water on the sand.
BLAST + SIXTEEN90 TANK MIXTURE	Sixteen90 + Blast Sprayable will reduce or eliminate drainage and crusting/hardness issues or conditions. Using the hand gun, wet the sand in the bunker with a solution of Sixteen90 at 2 quarts per 100 gallons of water plus Blast Sprayable at 1 gallon per 100 gallons of water. Repeat as needed to maintain sand bunkers.

Precautionary Statements/First Aid Measures in Case of Contact

DANGER: Toxic if swallowed.
DANGER: Causes severe skin burns and eye damage

- Avoid breathing vapors or mists.
- Avoid using product in a manner as to directly, or through drift, expose workers or other persons.
- Always consult the safety data sheet for specific instructions.
- Applicators and other handlers must wear goggles or a facial splash shield; chemical resistant gloves, such as nitrile rubber ≥ 14 mils or neoprene rubber ≥ 14 mils; coveralls or long sleeved shirt and trousers; shoes plus socks.
- Keep out of reach of children

First aid measures in case of contact

- **General Information:** Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation should be continued for at least 48 hrs after the accident.
- **EYE:** Rinse opened eye for several minutes under running water. Then consult a doctor. Call a doctor immediately. Remove contact lenses, if present. Hold eyelids apart and flush with water for at least 15 minutes.
- **SKIN:** Immediately wash with water and soap and rinse thoroughly.
- **INGESTION:** Immediately call a doctor. Drink large amounts of water and provide fresh air. Immediately call a doctor.

Precautionary Statements/First Aid Measures in Case of Contact (continued)

- **INHALATION:** In case of unconsciousness, place patient stably in side position for transportation.

Applicators and other handlers should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Remove protective clothing and equipment after handling. Wash the outside of gloves before removing. Wash thoroughly and change into clean clothing.

For technical information and Safety Data Sheet (SDS), contact Aquatrols at 1-800-257-7797 or visit our website at www.aquatrols.com.

IMPORTANT

Concentrated Blast Sprayable is corrosive. Application equipment should be POLYPROPYLENE or PVC (TYPE 1). Sprayers containing STAINLESS STEEL parts should be flushed with water immediately following use.

Storage and Disposal

- Store in original container only. Keep in a secure and locked storage area. Must NOT be disposed of together with household garbage. Do not allow product to reach sewage system.
- Disposal must be made in accordance with local, state, and federal regulations.

Condition of Sale Limited Warranty and Limitations of Liability and Remedies

Read the entire Directions for Use, Conditions, Disclaimer of Warranties and Limitations of Liability before using this product. If the terms are not acceptable, do not use the product and instead, return the unopened product container immediately. By using this product, you accept the following Conditions, Disclaimer of Warranties and Limitation of Liability.

For technical information, contact Aquatrols Corporation at 800-257-7797. Information regarding the contents and levels of metals in this product is available on the internet at www.aapfc.org/metals.html

CONDITIONS: The directions for use on this label are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risks associated with the use of this product. Insufficient performance or injury to the crop to which the product is applied may result from the occurrence of extraordinary or unusual weather conditions, the failure to follow the label directions or good application practices, all of which are beyond the control of Aquatrols Corporation. In addition, failure to follow label directions may cause poor performance, injury to crop, animals, human, or the environment. You assumed all such risks by using this product.

DISCLAIMER OF WARRANTIES: TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, AQUATROLS CORPORATION MAKES NO OTHER WARRANTIES OR REPRESENTATIONS OF ANY KIND, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT, INCLUDING NO IMPLIED WARRANTY OF

Condition of Sale (continued) Limited Warranty and Limitations of Liability and Remedies

MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE, THAT EXTEND BEYOND THE STATEMENTS MADE ON THIS LABEL AND NO SUCH WARRANTY SHALL BE IMPLIED BY LAW. No agent of Aquatrols Corporation is authorized to make any warranties beyond those contained herein or to modify the warranties contained herein. TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, Aquatrols Corporation disclaims any and all claims are waived any liability whatsoever for special, incidental or consequential damages or expense of any nature, including, but not limited to, loss of profit or income, resulting from the use or handling of this product.

LIMITATION OF LIABILITY: TO THE EXTENT CONSISTENT WITH APPLICABLE LAW, the remedy for any losses or cause of action relating to injuries, damages or the handling or use of this product, whether in contract, warranty, tort, negligence, strict liability or otherwise, shall not exceed the purchase price paid or, at Aquatrols Corporation's election, the replacement of the product. Aquatrols shall not be liable and any and all claims against Aquatrols are waived for special, indirect, incidental or consequential damages or expense of any nature, including, but not limited to, loss of profit or income.